18 VOLT HEAVY-DUTY 6-1/2" CIRCULAR SAWS

6310-22*

- FOR WOOD CUTTING APPLICATIONS

6320-22*

- FOR METAL CUTTING APPLICATIONS

DURABLE NICKEL PLATED STEEL SHOE To protect against scratching
PREMIUM BLADE FOR SMOOTH, BURR-FREE CUTTING.
CLEAR GUARD WINDOW FOR EXCELLENT LINE OF SIGHT

ALL 18 VOLT CIRCULAR SAWS FEATURE

- **18 Volt, 2.4 Amp-Hr Battery** Delivers long run time and is compatible with all other MILWAUKEE slide-on style battery 18 volt products.
- **One-Hour NiCd Charger** Charger is compatible with 12V, 14.4V and 18V slide-on style batteries.
- **Electric Brake For Quick Blade Stops**
- **Powerful Milwaukee Built Motor With Replaceable brushes**
- **3200 RPM For Fast Cutting**
- **Ergonomic Cushion Grip D-Handle** Keeps hands in comfortable position at all cutting depths.
- **All-Metal Upper And Lower Guards**
- **Superior Balance**
- **Large, Easy Access, Lower Blade Guard Lever**
- **Left Blade Provides The Best Line Of Sight**

6310-22 WOOD CUTTING CIRCULAR SAW FEATURES

- **Easily Cuts All 2X Material at 45° Bevel Angle**
- **Large 50° Bevel Capacity**

6320-22 METAL CUTTING CIRCULAR SAW FEATURES

- **Rugged Construction For Long, Trouble-Free Operation**
- **Spindle Lock And On-Board Hex Wrench For Easy Blade Change**
- **Common Materials Cut:** Conduit, Copper Pipe, Metal Studs , Unistrut And 'C' Channel, Plunge Cut And Fabricating Metal Duct Work, Angle Iron, Angle Steel, Black Pipe, Galvanized Pipe, Aluminum

SEE PAGE 118 FOR CIRCLE SAW BLADE SELECTION

* *TOOL AVAILABLE WITHOUT BATTERY, CHARGER OR CASE. SEE "-20" MODELS IN SPECIFICATIONS CHART BELOW*

SPECIFICATIONS

	CATALOG NUMBER	VOLTS DC	NO. OF BATTERIES INCLUDED	BATTERY CAPACITY AMP-HRS	NO LOAD RPM	ARBOR SIZE	DEPTH OF CUT AT 90°	DEPTH OF CUT AT 45°	DEPTH OF CUT AT 50°	LENGTH W/O BATTERY	LENGTH W/ BATTERY	NET WGT. LBS.	SHIP. WGT. LBS.
•	6310-20	18	0	—	3200	5/8"	2-1/8"	1-9/16"	1-13/32"	12-3/4"	15-1/2"	6.6 W/O BATTERY	8.1
	6310-22	18	2	2.4	3200	5/8"	2-1/8"	1-9/16"	1-13/32"	12-3/4"	15-1/2"	9.1 W/ BATTERY	26.9
•	6320-20	18	0	—	3200	5/8"	2-1/8"	–	–	11-1/4"	14"	6.4 W/O BATTERY	8.5
	6320-22	18	2	2.4	3200	5/8"	2-1/8"	–	–	11-1/4"	14"	8.9 W/ BATTERY	20.5

STANDARD EQUIPMENT: FOR 6310-20 • – Includes Circular Saw and 6-1/2" 24-Tooth Blade 48-40-4108 and Allen Wrench 49-96-0080. **FOR 6310-22 –** One-Hour NiCd Charger 48-59-0255, Two 18 Volt 2.4 Amp-Hr. Batteries, 6-1/2" 24-Tooth Blade 48-40-4108, Rip Fence Guide 49-22-1001, Allen Wrench 49-96-0080 and Impact Resistant Carrying Case. **FOR 6320-20 • –** Blade 48-40-4015 and Safety Glasses. **FOR 6320-22–** Metal Saw 6320-20, Blade 48-40-4015, Two Battery Packs 48-11-2230, One-Hour NiCd Charger 48-59-0255, Safety Glasses and Contractor Bag 48-55-3510.

• Tool only, less battery, charger and case.